



Representative Image

Ref. No. 102622 | Cat. No. MC1A310AT6

Description: Screw terminal 3P, AC3 4kW, 230V/50-60Hz AC Bifreq. Coil, 1NO (GE)

EAN 8425095026223

Home > Power devices > Contactors > 1. Series M: Compact contactor series 9-12A AC3

- Control circuit:
Alternating current up to 600V
Direct current up to 250V
- Terminal numbering in accordance with EN 50012
- Fixing by clipping onto 35mm DIN rail (EN 50022) or by screws
- Degree of protection IP20 in accordance with EN 60529
- Printed circuit version available
- Screws and fast-on terminals protected against accidental contact in accordance with VDE 0106 T.100 and VBG4
- Facility to mount instant and timed auxiliary contact blocks and voltage suppressor block
- Conform to IEC/EN60947-1, IEC/EN60947-4-1, IEC/EN60947-5-1

Descriptors

Category | 1. Series M: Compact contactor series 9-12A AC3

Specifications

Series	Three-pole contactors 6, 9 and 12 A (AC3)
Control circuit	AC
Frequency Control Voltage: AC	50-60 Hz
Control Voltage: AC (50/60 Hz)	220-230 V
Terminal	Screw terminal
Aux Contacts	1NO
Max. operating current AC3 Motors = 480V, 3-phase 50/60Hz	9 A
Package (pcs)	20
Terminal type	Screw terminal
Admissible power AC3 220V, 230V	3 kW
Admissible power AC3 380V, 400V	4 kW
Admissible power AC3 500V	4 kW
Max. operating current AC1 Non-inductive loads	20 A
Class	1. Contactors

Classifications

ETIM 5.0	EC000066
ETIM 6.0	EC000066

Dimensions

Weight	0.170 kg
--------	----------

Publications

Title	Publication No.	Publication Type
4-pole - Auxiliary contactor MC1A-MCRA (pdf)		
4-pole - Auxiliary contactor MC1A-MCRA (3DPDF format)	3D-00066-PDF	Drawings - CAD - 3D
4-pole - Auxiliary contactor MC1A-MCRA (stp)		
4-pole - Auxiliary contactor MC1A-MCRA (STEP format)	3D-00066	Drawings - CAD - 3D

Additional Documentation: Visit our [Publication Library](#) to find technical documentation, specifications, catalogues, promotional literature, 3D's,...